

EZDIVE SPIDER SPOOL USER GUIDE

EZDIVE SPIDER SPOOL /REEL USER GUIDE

Congratulations on your new acquisition of EZDIVE spool/reel used by cave, wreck, reef and deep explorers.

The Finger Spool is most often used as a Gap Reel or for Short Distance Exploration. Small and Low-Profile, a Spool fits nicely out of the way in a Pocket or Clipped-Off to a D-Ring. The Holes in the Side allow for Clipping in a Double-Ended Snap anywhere along the Perimeter of the Spool to keep the Line-Tight when not in use. Finger Spools come equipped with a

Durable Corrosion Resistant 4" (10.2 cm) Stainless Steel Double-Ender Bolt Snap with 18-8 Stainless Steel Internal Springs. The Spool is Injection-Molded with Glass-Filled Nylon for Strength and Long Life. The Line is 0.073" (1.86 mm) #24 Hi-Viz Nylon 16-Strand Braided Line with a Breaking Strength of 52kg. We have 3 choice of line colors Used as Gap Reel or for Short Distance Exploration Small and Low-Profile Fit in BCD Pocket or Clipped-Off to D-Ring Holes in Side: Clipping in Double-Ended

EZDIVE SPIDER POOL USER GUIDE

Snap to Keep Line-Tight

Durable Corrosion Resistant 4" (10.2 cm)

Stainless Steel Double-Ender Bolt Snap

Snap has 18-8 Stainless Steel Internal
Springs

Spool: Injection-Molded with Glass-Filled
Nylon for Strength and Long Life

Line: .073" (1.86 mm) #24 Hi-Viz Yellow

Nylon 16-Strand Braided Line

Line Breaking Strength: 52kg

Line length: 30m/50m



EZDIVE Spider 200 Reels were designed to be the best performing primary dive reels available. The Spool is Injection Molded using Glass Filled Nylon which is stronger than traditional ABS providing a Durable Core. This Core is bolted to an Aircraft Grade 6061-T6 Hard Anodized Aluminum Handle using a one piece Stainless Steel Shaft and is controlled by a Stainless Steel Lockdown Screw. All parts are engineered with the strictest tolerances which eliminate line traps or failures.

Spider 200 Reel with 200m of #24 Line
Advanced Materials and Construction

EZDIVE SPIDER SPOOL USER GUIDE

Handle Sized Appropriately for Both
Warm/Cold Water
6061-T6 Hard Anodized Aluminum
Glass Filled Nylon Spool

Marine Grade Stainless Steel
Components
Includes: Reel, Line, and Stainless Steel
Double Ended Bolt Snap

EZDIVE SPIDER 备用线轮使用指南

EZDIVE SPIDER 备用线轮/主线轮使用指南

百里挑一的产品！

感谢您购买休闲潜水员，洞穴，沉船和深潜潜水员广泛使用的 EZ SPIDER 线轮。请仔细阅读以下说明。该说明提供了许多关于产品使用以及保养的信息

如果有疑问欢迎通过邮件联系我们

ez_diving@hotmail.com

备用线轮

备用线轮通常作为释放水面标识浮标 (SMB) 或者在洞穴潜水中用于跳线使用。小并且简洁，备用线轮可以轻易被放到口袋中或者挂在 D 型环（不建议这么做，因为有可能脱

落）。可以使用双头扣来穿过线轮侧面的孔来固定线

备用线轮使用耐腐蚀的不锈钢双头扣以及 18-8 不锈钢弹簧。线轮外框使用注塑成型的玻璃填充尼龙，确保结实耐用。线使用型号 24(1.86 mm) 的高识别尼龙线。因为采用编织方法，所以能够承受大约 52 公斤的拉力。

特性

- 用于释放 SMB 或者洞穴跳线
- 小而轻巧
- 可以放在口袋
- 侧面的洞可以固定双头扣
- 有名字牌，可以写名字，作为视觉分辨参考

EZDIVE SPIDER 备用线轮使用指南

- 有凸起的 LOGO，可以作为无能见度时的触摸分辨参考（洞穴潜水用）

- 耐腐蚀的不锈钢扣
- 注塑成型的线轮外框保证解释耐用
- 型号 24(1.86 mm) 的高识别尼龙线，3

种颜色选择

- 尼龙线可承受拉力：52kg
- 线长度 30 米/50 米